



M 4-III/34

M 6-III/39

~~M 137 A/5~~

No. M 332/66

M 337/70

M 337 A/1

**INFORMATION BULLETIN**

**CONCERNS:** Serviceability of the aviation gasoline (petrol), mark AVGAS 100 L (Grade 100/130), for air service of the M 4-III, M 6-III, M 137 A, M 332, M 337 and M 337 A aeroengines.

**REASON :** Usable for air service in countries and regions where the above stated sort of aviation gasoline (petrol), containing a low percentage of lead tetraethyl (TEL), has been introduced into the aircraft fuel market.

In accordance with the Standard Regulation D.ENG. 2485 the specified percentage of lead tetraethyl (TEL) in the above stated sort of aviation gasoline equals to 2.0 ml/U.S.G. = 2.4 ml/I.G. = 0.0528 per cent by volume, not reaching the specified top limit 0.06 per cent by volume of TEL and, being thus serviceable for the above stated aeroengines.

**MEASURES:** No special measures arise through this Bulletin. However, the commercial users of the above stated engines are liable to follow the storage and other instructions of the gasoline producers.

Prague, December 28, 1973.

M. Adamec m.p.

.....  
Manufacturer's Representative

Ing. B. Homola m. p.

.....  
Customer's Representative  
at the Manufacturers

Ing. O. Holovský m. p.

.....  
State Aviation Inspection

Ing. F. Háva m. p.

.....  
OMNIPOL